

HYDROSLIDE FRAMELESS SLIDING SHOWER DOOR KITS

- Excellent Design for Compact Areas
- Clean, Sleek Lines
- Available in Four Stock Finishes, Custom Finishes Available
- Standard 180 Degree Installation is One Fixed Panel and One Door
- Custom Units Available

USE MONOLITHIC TEMPERED GLASS FOR GLASS THICKNESSES			
1/2" (12 MM)	3/8" (10 MM)	5/16" (8 MM)	1/4" (6 MM)
	✓	✓	

Hydroslide Sliding Shower Door Kits were designed for full standing showers or above bathtubs. The Hydroslide System can accommodate a wide range of shower designs with fixed glass panels on either end, or both sides at 90 or 180 degrees. The Hydroslide System also accommodates the option of floor-to-near-ceiling glass panels with a sliding door.

180 Degree Hydroslide Sliding Shower Door Kits feature the latest European 'all-glass' look. Kits are available in either 60" or 84" (1524 or 2134 mm) widths. Installers can cut the width to size, and height is optional as long as the sliding door glass weighs less than 88 pounds (40 kg). The 180 Degree Wall-to-Wall Installation only requires the 180 Degree Standard Kit for the installation.

90 DEGREE WALL-TO-WALL INSTALLATION
Uses our 180 Degree Standard Kit plus a 90 Degree Wall-to-Glass Accessory Kit

SUPGM SLIDING SHOWER DOOR SYSTEMS

90 Degree wall-to-glass installations require the 180 Degree Standard Kit, plus the 90 Degree Wall-to-Glass Accessory Kit. Individual or replacement parts can be seen on page 8. Bottom Fixed Glass Attachments and Handles or Knobs must be ordered separately.

Hydroslide Kits come in four finishes: Chrome Fittings with a Brite Anodized Sliding Track, Polished Brass with a Brite Gold Anodized Sliding Track, Brushed Nickel with Brushed Nickel Anodized Sliding Track, and Oil Rubbed Bronze with Oil Rubbed Bronze Anodized Sliding Track.

180 DEGREE WALL-TO-WALL INSTALLATION
Uses our 180 Degree Standard Kit

SPECIFICATIONS:

Materials: Plated or Lacquered Solid Brass Fittings; Anodized Aluminum Sliding Door Track
Glass Thickness Range: 3/8" or 5/16" (10 or 8 mm) Tempered Safety Glass (Not Included)
Maximum Door Weight: 88 lbs. (40 kg)
Glass Fabrication: Holes Required in Fixed Panel and Door
Include: Gaskets, Screws, and Glass Fabrication Information. Complete installation instructions, along with glass and metal cutting formula, available at crlaurence.com/shower-sliders

FINISHES:

-  Polished Chrome
-  Polished Brass
-  Brushed Nickel
-  Oil Rubbed Bronze

180 DEGREE STANDARD KIT 60" (1524 MM) CAT. NO.	180 DEGREE STANDARD KIT 84" (2134 MM) CAT. NO.	90 DEGREE WALL-TO-WALL ACCESSORY KIT CAT. NO.	FINISH
HYDK60CH	HYDK84CH	HYDA9CH	Brite Anodized/Chrome
HYDK60BR	HYDK84BR	HYDA9BR	Brite Gold Anodized/Brass
HYDK60BN	HYDK84BN	HYDA9BN	Brushed Nickel
HYDK60RB	HYDK84RB	HYDA9RB	Oil Rubbed Bronze

SUPGM SLIDING SHOWER DOOR SYSTEMS